

Product Name:
Superclear TerraLock Mulch Glue

Superclear TerraLock Mulch Glue is a high-quality waterbased acrylic emulsion designed to spray onto your mulch beds to keep them where you want them and off your sidewalks and walkways. The material allows for great permeability to the soil below while still maintaining the integrity of the mulch bed, preventing its dispersal by rain, gutter-wash, animals, and even pets. The material contains powerful UV inhibitors to maintain the nice colorful look of freshly laid mulch not yet bleached by sunlight. The material is good for the environment, prevents erosion, and is non-toxic and safe for people, pets, plants and wildlife.

	Key Points
Description	Single component, waterbased, 100% cross linking acrylic sealer
Resistance	Excellent Weathering and UV Resistance. Does not yellow. Seals and protects mulch from color loss and brings back some color to old mulch. Seals rocks and aggregates and includes a moldicide to prevent discoloration. For best results, recommended application on new stone, mulch and aggregates.
Durability	Long Lasting. Can last up to 3 years in moderate environments. The harsher the environment the less lifespan.
Stabilizes	Mulch, Pea Gravel, Pine Straw, Pine Bark, sand and loose soils
Concentrated	Accepts up to 50 % additional water, this will thin the product and allow for better penetration, but will negatively affect the bonding capabilities the more it is diluted.
Application	Pour product into a pump sprayer. Adjust nozzle for better coverage. Spray and walk away.
Dry Time	4-6 hours after application. The warmer and drier the environment, the faster it will cure/dry.
Clean up	Soap and Water while wet



SAINT PETERSBURG:
 4301 A 34th Street North
 St. Petersburg, FL 33714
 Office: (727) 327-8117

FORT LAUDERDALE:
 5553 Anglers Ave Suite 105
 Fort Lauderdale, FL 33312
 Office: (954) 527-9200



Part Number	157021, 157022, 157023
-------------	------------------------

This material is for professional use only, using adequate ventilation and protection from eye and skin exposure. Any information supplied with this material is given in good faith but should be verified by the end user, as is the suitability of the material for their application. The warranty of this material shall be limited to the replacement of defective material.